

SCREENING RANGE

KESTREL 600



FEEDER

7m³ (9.2yd³) Hopper capacity (with grid)
102mm (4") Grid aperture as standard; 152mm (6") optional

SCREEN

2.44m x 1.22m (8' x 4') Double deck screen
Hydraulic screen angle adjustment (25-35 degrees)
End tensioned as standard

POWERUNIT

Tier 3: DEUTZ 2011 49.4kW/66Hp @2300rpm
Tier 4 Final: CAT C3.4 engine (55kW / 74hp @ 2300rpm)

OUTPUT POTENTIAL

Up to 200tph / 220 US tph

CONVEYORS

800mm (32") Variable speed feed conveyor

800mm (32") Variable speed product conveyor
1050mm Wide fines conveyor with discharge of 3.18m (10'5") on the tracked variant; 3.43m (11'3") on the wheeled variant

650mm (26") Wide midgrade and oversize conveyors with discharge of 3.44m (11'3") on the tracked variant; 3.64m (11'11") on the wheeled variant

TRANSPORT

Transport dimensions (with Grid)

	LENGTH	WIDTH	HEIGHT
Track Unit	12.48 (40'11")	2.68m (8'8")	3.28m (10'9")
Wheeled	13m (42'7")	2.75m (9')	3.5m (11'7")

Weight (Track with Grid): 15,200Kgs (33,510lbs)

Weight (Wheeled with Grid): 14,000Kgs (30,865lbs)